

# Ashitech

## BITUMEN SPRAYER



### SALIENT FEATURES :

1. FULLY INSULATED TANK WITH HIGH PERFORMANCE OIL HEATING.
2. AIR COOLED DIESEL ENGINE AND POSITIVE DISPLACEMENT GEAR PUMP.
3. FULLY-CIRCULATING SPRAY BAR.
4. OPERATOR'S PLATFORM WITH HOOD.
5. SIMPLE PRESSURE CLEANING SYSTEM PROVIDED.
6. DIGITAL SPEED INDICATOR.
7. MOISTURE SEPARATOR FOR CLEAN & DRY AIR.

# TECHNICAL DATA

## BITUMEN TANK :

- MODEL : ABS - 4000 / ABS - 6000
- CAPACITY : 4000 / 6000 Litres.
- TANK SHAPE : Oval
- INSULATION : 50 mm Thick Glass wool
- TEMPERATURE GAUGE : 0-300° C
- MANHOLE : 450 mm Dia.
- MOUNTING : Tank Mounted on any truck chachis of wheel base 176"/166"

## SPRAY BAR :

- LENGTH : 2.5 mtr.
- LENGTH WITH EXTENSION : 4.00 mtr.
- CONTROL OF SPRAY BAR : Pneumatically operated
- PRE-HEATING OF SPRAY BAR : Fully circulating of pre-heated Bitumen
- BITUMEN SPRAYING PRESSURE : 0-4 Kg. / cm<sup>2</sup>

## BITUMEN PUMP :

- 2" x 2" size positive displacement gear pump with output of 400 Ltrs/Min.

## AIR COMPRESSOR :

- Standard make 2 Cyl. Air compressor

## BURNER :

- FUEL CONSUMPTION : 20 Ltr. / hr

## FUEL TANK :

- 130 Ltrs. capacity

## ENGINE :

- Standard make Air cooled diesel engine

# ASHITECH EQUIPMENTS PVT. LTD.

Manufacturer of Road Construction Equipments

Regd. Office : Plot No. 14, G.I.D.C. II, Dediyanan, Mehsana-384004, Gujarat, INDIA.

Telefax : +91-2762-224050, 224051

Web site : [www.ashitech.com](http://www.ashitech.com)

E-mail : [ashirvad\\_ashitech@yahoo.co.in](mailto:ashirvad_ashitech@yahoo.co.in), [ashirvad11@gmail.com](mailto:ashirvad11@gmail.com)